



HENSEL

PASSION FOR POWER.

The new black series
DK Cable junction boxes

for proper installation with black cables



More information at www.hensel.in

 made in **GERMANY**
Since 1931

DK Cable junction boxes
For normal environment and protected outdoor
Cable entry via integrated elastic membranes




DK 0202 B NEW
0.75-2.5 mm², Cu 3~

- terminal with 2 clamping units per pole
- 5-pole per pole 8 x 0,75 mm² sol / f, 6 x 1,5 mm² sol / f, 4 x 2,5 mm² sol / f, 2 x 4 mm² sol / f
- with integrated elastic membranes, which can be removed for cable entry via cable glands, sealing range 6.0-15.0 mm
- with one cable entry in the bottom, sealing range Ø 6.0-13.0 mm
- lid fasteners sealable without accessories
- retaining strap and external brackets for wall fixing included

rated insulation voltage	U _i = 690 V a.c./d.c.
rated current	20 A
material	PP (polypropylene)

IP
66




DK 0404 B NEW
1.5-4 mm², Cu 3~

- terminal with 2 clamping units per pole
- 5-pole per pole 8 x 1,5 mm² sol / f, 6 x 2,5 mm² sol / f, 4 x 4 mm² sol / f, 2 x 6 mm² sol / f
- with elastic membranes, which can be removed for cable entry via cable glands, sealing range 9.0-17.0 mm
- with one cable entry in the bottom, sealing range Ø 6.0-15.0 mm
- lid fasteners sealable without accessories
- retaining strap and external brackets for wall fixing included

rated insulation voltage	U _i = 690 V a.c./d.c.
rated current	32 A
material	PP (polypropylene)

IP
66




DK 0606 B NEW
2.5-6 mm², Cu 3~

- terminal with 2 clamping units per pole
- 5-pole per pole 6 x 1,5 mm² sol / f, 4 x 2,5 mm² sol / f, 4 x 4 mm² sol / f, 4 x 6 mm² sol / f, 2 x 10 mm² sol / f
- with elastic membranes, which can be removed for cable entry via cable glands, sealing range 9.0-21.0 mm
- with one cable entry in the bottom, sealing range Ø 9.0-20.0 mm
- lid fasteners sealable without accessories
- retaining strap and external brackets for wall fixing included

rated insulation voltage	U _i = 690 V a.c./d.c.
rated current	40 A
material	PP (polypropylene)

IP
66




DK 1010 B NEW
4-10 mm², Cu 3~

- terminal with 2 clamping units per pole
- 5-pole per pole 6 x 2.5 mm² sol, 4 x 4 mm² sol, 4 x 6 mm² sol, 4 x 10 mm² sol, 2 x 16 mm² s
- with elastic membranes, which can be removed for cable entry via cable glands, sealing range 9.0-21.0 mm
- with two cable entries in the bottom, sealing range Ø 9.0-20.0 mm
- lid fasteners sealable without accessories
- retaining strap and external brackets for wall fixing included

rated insulation voltage	U _i = 690 V a.c./d.c.
rated current	63 A
material	PP (polypropylene)

IP
66



DK Cable junction boxes
For normal environment and protected outdoor
Cable entry via integrated elastic membranes




DK 0200 B NEW

- without terminals
- with integrated elastic membranes, which can be removed for cable entry via cable glands, sealing range 6.0-15.0 mm
- with one cable entry in the bottom, sealing range Ø 6.0-13.0 mm
- lid fasteners sealable without accessories
- retaining strap and external brackets for wall fixing included

rated insulation voltage	$U_i = 1000 \text{ V a.c./d.c.}$
material	PP (polypropylene)

IP
66




DK 0400 B NEW

- without terminals
- with elastic membranes, which can be removed for cable entry via cable glands, sealing range 9.0-17.0 mm
- with one cable entry in the bottom, sealing range Ø 6.0-15.0 mm
- lid fasteners sealable without accessories
- retaining strap and external brackets for wall fixing included

rated insulation voltage	$U_i = 1000 \text{ V a.c./d.c.}$
material	PP (polypropylene)

IP
66




DK 0600 B NEW

- without terminals
- with elastic membranes, which can be removed for cable entry via cable glands, sealing range 9.0-21.0 mm
- with one cable entry in the bottom, sealing range Ø 9.0-20.0 mm
- lid fasteners sealable without accessories
- retaining strap and external brackets for wall fixing included

rated insulation voltage	$U_i = 1000 \text{ V a.c./d.c.}$
material	PP (polypropylene)

IP
66




DK 1000 B NEW

- without terminals
- with elastic membranes, which can be removed for cable entry via cable glands, sealing range 9.0-21.0 mm
- with two cable entries in the bottom, sealing range Ø 9.0-20.0 mm
- lid fasteners sealable without accessories
- retaining strap and external brackets for wall fixing included

rated insulation voltage	$U_i = 1000 \text{ V a.c./d.c.}$
material	PP (polypropylene)

IP
66



Accessories



Cable retention via retention rings for cables



The range

DK Cable junction boxes

The most suitable solution for every application.



DK series: IP 66
for normal environment and protected outdoor
integrated elastic membranes or metric knockouts



KF series: IP 66 / IP 67 / IP 69
weatherproof, for outdoor installation
metric knockouts



WP series: IP 68
submersion up to 20 meters, 168 hours
watertproof, for encapsulation
metric knockouts



FK series:
E30/E60/E90 intrinsic fire resistance
PH120 insulation integrity



Hensel Electric India Pvt Ltd

Industrial Electrical Power Distribution Systems

35 Kunnam Village, Sunguvarchathram
Walajabad Road
Sriperumbudur - 631 604
Kanchipuram Dist., Tamil Nadu
INDIA

Phone: +91-44-3727 0202
Fax: +91-44-3727 0200
E-Mail: info@hensel-electric.in
www.hensel.in

02/2020

made in **GERMANY**
since 1931